

Mitsutomo Submittal Data Sheet

9k High Heat One Way Cassette Multi Zone Heat Pump System

Job Name: _____

Engineer: _____

Submitted By: _____

Date: _____

Unit Tag: _____

System Info & Features:

- One way ceiling cassette heat pumps
- Fits between most ceiling joists
- Large display and handheld remote
 - 24 hour timer
 - Error code diagnosis
 - Functions settings (see manual)
- 7-Day Programmable wall mount wifi thermostat with infrared
- Economy mode
- Turbo mode
- Dry mode
- Heating down to -22 degrees
- Drop down filter



MODEL NUMBER	
Indoor unit:	HJ-UZ09-AB-Q
Certified:	

OPTIONAL ACCESSORIES	
Wifi Adapter	17310900A02901
3rd Party Thermostat Interface Adapter	17222000A68532

SYSTEM PERFORMANCE DATA	
Electrical:	
Normal Operational Voltage (V, Ph, Hz)	208/230V, 1Ph, 60Hz
Connection wiring	14/4 STRANDED
Cooling Efficiencies & Capacity Data:	
Nominal Capacity (Btu/h)	9000
*See Outdoor Unit for Rated Capacities	

INDOOR UNIT DATA	
Input (W)	/
Output (W)	30.0
Speed(Hi/Mi/Lo) (RPM)	1024/944/784
Air Flow & Sound Data:	
Indoor air flow (Hi/Med/Lo) (CFM)	341.18/294.12/258.82/235.29
Indoor noise level (Hi/Med/Lo) (DBA)	37.5/35.5/31
Dry Mode (Dehumidification) (LPH)	1.02

REFRIGERANT PIPE DATA	
Refrigerant type	R410A
Design pressure (PSIG)	550/340
Liquid side / Gas side (inch)	1/4" / 3/8"
Connection method	Flared
Temperature Ratings:	
Indoor (cooling) (Deg. °F)	60~90
Indoor (heating) (Deg. °F)	62~86
Freeze mode (Deg. °F)	32

DIMENSIONS	
Indoor:	
Dimension (WxDxH) (inch)	50.31x13.19x8.98
Packing(WxDxH) (inch)	57.60x22.48x22.64
Net/Gross weight (lbs.)	43.87/81.35

WARRANTY	
	5 years compressor 5 years parts

Indoor Unit Dimension

