

## Mitsutomo Submittal Data Sheet

### R-454B 6k 1 Way Cassette Multi Zone Heat Pump System

Job Name: \_\_\_\_\_

Engineer: \_\_\_\_\_

Submitted By: \_\_\_\_\_

Date: \_\_\_\_\_

Unit Tag: \_\_\_\_\_

#### System Info & Features:

- One way ceiling cassette heat pumps
- Fits between most ceiling joists
- Large display and handheld remote
  - 24 hour timer
  - Error code diagnosis
  - Functions settings (see manual)
- 7-Day Programmable wall mount wifi thermostat with infrared
- Economy mode
- Turbo mode
- Dry mode
- Heating down to -22 degrees
- Drop down filter



#### MODEL NUMBER

Indoor unit: HJ-UZ06-LA-Q

Certified:

#### OPTIONAL ACCESSORIES

3rd Party Thermostat Interface Adapter 17222000A68532

#### SYSTEM PERFORMANCE DATA

Electrical:		
Normal Operational Voltage	(V, Ph, Hz)	208/230V,60Hz,1Ph
Connection wiring		14/4
Performance Data:		
Rated Capacity		6500
Min/Max Capacity		3600~11200
Moisture Removal	(L/H)	0.34

#### INDOOR UNIT DATA

Fan Motor	(RLA)	0.8
Fan Motor	(W)	30

#### Air Flow & Sound Data:

Indoor Air Flow (Turbo/H/M/L/Q)	(CFM)	341.4 / 294.3 / 259.0 / 235.4 / 235.4
Indoor Noise Level (Turbo/H/M/L/Q)	(DBA)	46.5 / 37.5 / 35.5 / 26 / 23.5

#### REFRIGERANT PIPE DATA

Refrigerant Type		R454B
Liquid Side	(inch)	1/4
Gas Side	(inch)	3/8
Connection Method		Flared
Temperature Ratings:		
Indoor (cooling)	(Deg. °F)	-22~122
Indoor (heating)	(Deg. °F)	-22~75

#### Dimensions:

Indoor:		
Dimension (WxDxH)	(inch)	50.31 x 13.19 x 8.98
Packing(WxDxH)	(inch)	57.60 x 22.48 x 22.64
Unit weight	(lbs.)	45.19
Shipping Weight	(lbs.)	82.45

#### WARRANTY



5 years compressor  
5 years parts

### Indoor Unit Dimension (External Pump)

