

Mitsutomo Submittal Data Sheet

R-454B 9K High Heat Multi Zone Wall Mounted Heat Pump

Job Name: _____

Engineer: _____

Submitted By: _____

Date: _____

Unit Tag: _____

System Info & Features:

- Large display handheld remote
 - 24 hr timer
 - Error code diagnosis
 - Functions settings (see manual)
- Economy mode
- Turbo mode
- Dry mode



MODEL NUMBER	
Indoor unit:	HW-UZ09-LA-Q
Certified:	   

OPTIONAL ACCESSORIES	
3rd Party Thermostat Interface Adapter	17222000A68532

SYSTEM PERFORMANCE DATA		
Electrical:		
Normal Operational Voltage	(V, Ph, Hz)	208/230V,60Hz,1Ph
Connection wiring		14/4
Performance Data:		
Rated Capacity		9000
Min/Max Capacity		3600~13500
Moisture Removal	(L/H)	0.6


INDOOR UNIT DATA		
Fan Motor	(RLA)	0.5
Fan Motor	(W)	13
Air Flow & Sound Data:		
Indoor Air Flow (Turbo/H/M/L/Q)	(CFM)	382.6 / 294.3 / 194.2 / 153.0 / 153.0
Indoor Noise Level (Turbo/H/M/L/Q)	(DBA)	39.5 / 39.5 / 33 / 24 / 20.5

REFRIGERANT PIPE DATA		
Refrigerant Type		R454B
Liquid Side	(inch)	1/4
Gas Side	(inch)	3/8
Connection Method		Flared
Temperature Ratings:		
Indoor (cooling)	(Deg. °F)	-22~122
Indoor (heating)	(Deg. °F)	-22~75

Dimensions:		
Indoor:		
Dimension (WxDxH)	(inch)	31.57 x 7.87 x 11.61
Packing(WxDxH)	(inch)	34.45 x 11.22 x 14.96
Unit weight	(lbs.)	18.96
Shipping Weight	(lbs.)	24.25

WARRANTY	
	5 years compressor 5 years parts

Indoor Unit Dimension (External Pump)



Capacity	W	D	H
9k	31.57	7.87	11.61