

## Mitsutomo Submittal Data Sheet

### R-454B 12K Multi Zone Floor Console High Heat Series

Job Name: \_\_\_\_\_

Engineer: \_\_\_\_\_

Submitted By: \_\_\_\_\_

Date: \_\_\_\_\_

Unit Tag: \_\_\_\_\_

#### System Info & Features:

- Compact Design
- Dual Air Outlets
- Refrigerant leakage detection sensor
- Humidity sensor
- 1~100% fan speed setting
- Heating down to -22°
- WiFi Compatible (with dongle)
- Large Handheld Remote
- 7 Day Wifi Programmable Wall Thermostat



MODEL NUMBER	
Indoor unit:	HL-UZ12-LA-Q
Certified:	   

OPTIONAL ACCESSORIES	
Wifi Adapter	17310900A02901
3rd Party Thermostat Interface Adapter	17222000A68532

SYSTEM PERFORMANCE DATA		
<b>Electrical:</b>		
Normal Operational Voltage	(V, Ph, Hz)	208/230V,60Hz,1Ph
Connection wiring		14/4
<b>Performance Data:</b>		
Rated Capacity		12000
Min/Max Capacity		3700~14000
Moisture Removal	(L/H)	1.48

INDOOR UNIT DATA		
Fan Motor	(RLA)	0.5
Fan Motor	(W)	13
<b>Air Flow &amp; Sound Data:</b>		
Indoor Air Flow (Turbo/H/M/L/Q)	(CFM)	441.4 / 376.7 / 323.7 / 188.4 / 129.5
Indoor Noise Level (Turbo/H/M/L/Q)	(DBA)	44 / 40.5 / 37 / 26.5 / 24

REFRIGERANT PIPE DATA	
Refrigerant Type	R454B
Liquid Side	(inch) 1/4
Gas Side	(inch) 3/8
Connection Method	Flared
<b>Temperature Ratings:</b>	
Indoor (cooling)	(Deg. °F) -22~122
Indoor (heating)	(Deg. °F) -22~75

DIMENSIONS:		
<b>Indoor:</b>		
Dimension (WxDxH)	(inch)	31.26 x 7.87 x 24.45
Packing(WxDxH)	(inch)	34.06 x 11.02 x 28.31
Unit weight	(lbs.)	32.85
Shipping Weight	(lbs.)	41.89

WARRANTY	
	5 years compressor 5 years parts

### Indoor Unit Dimension (External Pump)

