

Mitsutomo Submittal Data Sheet

R-454B 18K Multi Zone Floor Console High Heat Series

Job Name: _____

Engineer: _____

Submitted By: _____

Date: _____

Unit Tag: _____

System Info & Features:

- Compact Design
- Dual Air Outlets
- Refrigerant leakage detection sensor
- Humidity sensor
- 1~100% fan speed setting
- Heating down to -22°
- WiFi Compatible (with dongle)
- Large Handheld Remote
- 7 Day Wifi Programmable Wall Thermostat



MODEL NUMBER	
Indoor unit:	HL-UZ16-LA-Q
Certified:	   

OPTIONAL ACCESSORIES	
Wifi Adapter	17310900A02901
3rd Party Thermostat Interface Adapter	17222000A68532

SYSTEM PERFORMANCE DATA		
Electrical:		
Normal Operational Voltage	(V, Ph, Hz)	208/230V,60Hz,1Ph
Connection wiring		14/4
Performance Data:		
Rated Capacity		16000
Min/Max Capacity		6500~17200
Moisture Removal	(L/H)	2.18

INDOOR UNIT DATA		
Fan Motor	(RLA)	1.0
Fan Motor	(W)	13
Air Flow & Sound Data:		
Indoor Air Flow (Turbo/H/M/L/Q)	(CFM)	500.3 / 441.4 / 382.6 / 323.7 / 206.0
Indoor Noise Level (Turbo/H/M/L/Q)	(DBA)	47 / 43.5 / 40.5 / 30.5 / 25.5

REFRIGERANT PIPE DATA		
Refrigerant Type		R454B
Liquid Side	(inch)	1/4
Gas Side	(inch)	1/2
Connection Method		Flared
Temperature Ratings:		
Indoor (cooling)	(Deg. °F)	-22~122
Indoor (heating)	(Deg. °F)	-22~75

DIMENSIONS:		
Indoor:		
Dimension (WxDxH)	(inch)	31.26 x 7.87 x 24.45
Packing(WxDxH)	(inch)	34.06 x 11.02 x 28.31
Unit weight	(lbs.)	32.85
Shipping Weight	(lbs.)	41.89

WARRANTY	
	5 years compressor 5 years parts

Indoor Unit Dimension (External Pump)

