

Mitsutomo Submittal Data Sheet

Smart Thermostat Submittal

Job Name: _____

Engineer: _____

Submitted By: _____

Date: _____

Unit Tag: _____

FEATURES & FUNCTIONS

Basic functions

- TFT 4 inch touch screen
- Temperature and humidity sensor
- Motion sensor(Detection distance: 1m)
- Schedule
- App remote control
- Fahrenheit/Celsius
- Screen Clean
- Speaker

- Weather Forecast
- Comfort Presets
- Vacation

OTA HA HB Communication

- Mode: Dual Auto-Heat-Cool-Fan-Emergency Heat
- Fan speed: Auto-Low-Med-High
- Dehumidification
- iCheck

iService

- Update IDU software
- Freeze Protection R Rc 24V
- Conventional(2H/2C)-Boiler,Furnace,electric(2 stage heating)
- Heat pumps (2 stage heat pump + 2 stage aux heat) (4H/2C).Dual-Fuel support.
- Wires detection
- Mode: Dual Auto-Heat-Cool-Emergency Heat

MODEL NUMBER

Model: MT-STATIQ-02

SYSTEM PERFORMANCE AND DATA

Power supply	V	HA-HB: Max 20Vdc	R-Rc : 24Vac
Ambient Temperature	°F	32-95	
Ambient Humidity	RH	30%-80%	
Material	Front panel: glass Back panel: PC/ABS		

DIMENSIONS

Dimension (W×D×H)	(in)	4 x 1 x 4
Net Weight	(lbs)	.45



Unit Dimension

